

Magma 4102



Magma

Magma 4102 is a highly efficient luminaire optimised for T5-light source.

An excellent choice for industries, warehouses, and supermarkets.

Can be fitted with an aluminium louvre/anti-glare protection, easily fixed to the luminaire body. Mounted by means of wire attachment or direct to the luminaire body. Screwless connection over a 5-pole terminal block (2.5 mm²) for through-wiring. Magma is also available with the reflector anti-glare protection DP+R (4162).



Wire attachment No. 348



Wire attachment No. 343



Luminaire 4182 equipped with an aluminium louvre

Magma 4102



Aluminium louvre
4182/54




Wire attachment No. 343




Wire attachment No. 348

Polar diagram



4102



4182
(incl. Louvre)

Facts

Luminaire:

Body and end-pieces of hot-galvanized sheet steel.

Reflector:

Reflector of aluminium with a super-gloss anodised finish for highest efficiency.

Louvre:

The luminaire can be provided with glare protection (E7221912, E7221914), for good protection along the luminaire. Dimmer angle 15°.

Connection:

At the end-pieces through cable entry Ø23mm with blanking grommet. The luminaire has a through-wiring facility 5x2.5mm².

Installation:

Surface mounting or to a wire using wire attachment No. 343 or No. 348 (see accessories).

Miscellaneous:

The luminaires are provided with electronic ballast units (HF). Available with effect 2x28, or 2x35. Body and end-piece also available in a powder coated white finish.

Dimensions and weights

Effect	Length	Width	Height	Suspension c/c	Weight
2x49w	1596	150	94	1570	3,4kg
2x54w	1296	150	94	1270	4,0kg

All dimensions in mm.

Subject to changes of design and dimensions without notice.

Luminaire:

E72 219 02	Magma 4102/54	2x54w T5
E72 219 04	Magma 4102/49	2x49w T5

Accessories:

E79 201 44	Wire attachment No. 343
E79 218 00	Wire attachment No. 348
E72 219 12	Louvre 4182/54
E72 219 14	Louvre 4182/49